

**PHYSICAL PROPERTIES:**

52"/54" (132/137 CM) Vinyl Wallcovering, Type II

Total Weight: 20 oz./lin. yard (619 G/PLM)

13.3 oz./sq. yard (451 G/PSM)

Repeat: Horizontal 5-1/8" x Vertical 34-7/8"

All patterns are stocked in 30 linear yard bolts and must be ordered in 15 yard increments.

**MYLAR COLOURS:** CD2-ALO-13, CD2-ALO-23, CD2-ALO-24

Backing: Nonwoven • Class "A" Fire Rated • Flame Spread 25 • Smoke Development 55

*These sku's are constructed with Mylar and have special installation instructions.*

*Please visit our website at [colouranddesign.com](http://colouranddesign.com) and download instructions prior to installation.*

**ALL REMAINING COLOURS**

Backing: Osnaburg • Class "A" Fire Rated • Flame Spread 15 • Smoke Development 10

**FIRE HAZARD CLASSIFICATION RESULTS:**

Tested in accordance with ASTM E-84 Tunnel Test

In addition, this product meets Type II CCC-W-408A through D requirements for Washability, Scrubbability, Abrasion Resistance and Stain Resistance

**SUSTAINABILITY, ENVIRONMENT AND HEALTH:**

- Meets California 01350 IAQ test requirements for wallcovering
- USGBC LEED
  - Can contribute to CI/NC LEED® EQ 4.1 Low Emitting Materials: Adhesives and Sealants.
  - Can contribute to CI/NC LEED® EQ 4.2 Low Emitting Materials: Paints and Coatings.
  - Can contribute to CI/NC LEED® MR 5.1 Regional Material: 20% manufactured regionally within 500 miles of jobsite.
  - Can contribute to CI/NC LEED® MR 4 building Product Disclosure and Optimization:
  - Published Health Product Declaration (HPD)

All installations must conform to Colour & Design's current Hanging Instructions and Product Technical information.

**ANTI-MICROBIAL FEATURES:**

This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

**BREATHE FREE™ MICRO-VENTING AVAILABLE UPON REQUEST:**

Breathe Free™ Micro-vented wallcovering from Colour & Design can be used to help control un-wanted moisture inside a building envelope.

*Breathe Free™ Micro-vented wallcovering is not available for MYLAR COLOURS: CD2-ALO-13, CD2-ALO-23, CD2-ALO-24.*

**LIMITED WARRANTY:**

5 year warranty against manufacturing defects.

**INSTALLATION NOTE**

**Alotian** is a reverse match pattern

For specifications and hanging instructions go to: [www.colouranddesign.com](http://www.colouranddesign.com)