

<b>Physical Properties:</b>	<b>Total Weight</b>	<b>U.S. Units</b>	<b>Metric Units</b>
		20 oz./LY	619 G/PLM
		13.3 oz./SQ	451 G/PSM
	<b>Fabric Type</b>	Non-Woven	
	<b>Material Width</b>	52/54"	132/137 cm
	<b>Repeat</b>	Horizontal 54" x Vertical 24"	

**Federal Specifications:** Colour&Design Vinyl Wallcovering meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

**Fire Hazard Classification Results:** **ASTM E-84** Tunnel Test: Class A, Flame Spread: 15; Smoke Developed: 15  
Passes NFPA 286 Corner Burn Test

- Performance Features:**
- Phthalate-free
  - No heavy metals or formaldehyde
  - Printed with low VOC inks
  - Five year warranty against materials defects

- Environmental Attributes:**
- Ultra-low emitting – Pass rating under CA 01350
  - NSF/ANSI 342 certified for sustainability

**Permeability, Moisture and Mold:** Contains anti-microbial additives to resist the grown of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

**INSTALLATION NOTE**  
**BOKA BLOOM™** is a reversible match pattern  
 For specifications and hanging instructions go to: [www.colouranddesign.com](http://www.colouranddesign.com)