

Physical Properties:	Total Weight	U.S. Units	Metric Units
		20 oz./LY	619 G/PLM
		13.3 oz./SQ	451 G/PSM
	Fabric Type	Osnaburg	
	Material Width	52/54"	132/137 cm
	Repeat	Horizontal 54" x Vertical 18"	

Federal Specifications: Colour&Design Vinyl Wallcovering meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

Fire Hazard Classification Results: **ASTM E-84** Tunnel Test: Class A, Flame Spread: 15; Smoke Developed: 20

- Performance Features:**
- Phthalate-free
 - No heavy metals or formaldehyde
 - Printed exclusively with water-based, low VOC inks
 - Microventing for permeability is available on a custom order basis
 - Five year warranty against materials defects

- Environmental Attributes:**
- Ultra-low emitting – Pass rating under CA 01350
 - NSF/ANSI 342 certified for sustainability
 - CA Prop 65 compliant

Permeability, Moisture and Mold: Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration. Breathe Free™ Micro-vented wallcovering from Colour&Design Wall can be used to help control un-wanted moisture inside a building envelope.

INSTALLATION NOTE
Boka Grid™ is a random match reversible pattern
 For specifications and hanging instructions go to: www.colouranddesign.com