

SKUS: CD-CRW-201, CD-CRW-202, CD-CRW-203, CD-CRW-204, CD-CRW-205, CD-CRW-206

PHYSICAL PROPERTIES:

52"/54" (132/137 CM) Vinyl Wallcovering, Type II

Total Weight: 20 oz./lin. yard (620 G/PLM)

13.3 oz./sq. yard (451 G/PSM)

Backing: Osnaburg

All patterns are stocked in 30 lineal yard bolts and must be ordered in 15 yard increments.

FIRE HAZARD CLASSIFICATION RESULTS:

Tested in accordance with ASTM E-84 Tunnel Test

Class "A" Fire Rated

Flame Spread 20

Smoke Developed 45

In addition, this product meets Type II CCC-W-408D & W-101 requirements for Washability, Scrubbability, Abrasion Resistance and Stain Resistance

SUSTAINABILITY, ENVIRONMENT AND HEALTH:

- Meets California 01350 IAQ test requirements for wallcovering
- USGBC LEED

Can contribute to CI/NC LEED® EQ 4.1 Low Emitting Materials: Adhesives and Sealants.

Can contribute to CI/NC LEED® EQ 4.2 Low Emitting Materials: Paints and Coatings.

Can contribute to CI/NC LEED® MR 5.1 Regional Material: 20% manufactured regionally within 500 miles of jobsite.

All installations must conform to Colour & Design's current Hanging Instructions and Product Technical information.

ANTI-MICROBIAL FEATURES:

This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

BREATHE FREE™ MICRO-VENTING AVAILABLE UPON REQUEST:

Breathe Free™ Micro-vented wallcovering from Colour & Design can be used to help control un-wanted moisture inside a building envelope.

LIMITED WARRANTY:

5 year warranty against manufacturing defects.

INSTALLATION NOTE

Random / Reversible match pattern

For specifications and hanging instructions go to: www.colouranddesign.com