

SKUS: CD-CRW-227, CD-CRW-228, CD-CRW-229, CD-CRW-230, CD-CRW-231

PHYSICAL PROPERTIES:

52"/54" (132/137 CM) Wallcovering, Type II

Total Weight: 20 oz./lin. yard (619 G/PLM)

13.3 oz./sq. yard (451 G/PSM)

Backing: Non-woven

All patterns are stocked in 30 lineal yard bolts and must be ordered in 15 yard increments.

FIRE HAZARD CLASSIFICATION RESULTS:

Tested in accordance with ASTM E-84 Tunnel Test

Class "A" Fire Rated

Flame Spread 25

Smoke Developed 55

In addition, this product meets Type II CCC-W-408A through D & W-101 requirements for Washability, Scrubbability, Abrasion Resistance and Stain Resistance

SUSTAINABILITY, ENVIRONMENT AND HEALTH:

- Meets California 01350 IAQ test requirements for wallcovering
- Can contribute to LEED® EQ 4.1 point for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives
- Can contribute to LEED® MR 5.1 point for regional materials

All installations must conform to Colour & Design's current Hanging Instructions and Product Technical information.

ANTI-MICROBIAL FEATURES:

This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

BREATHE FREE™ MICRO-VENTING AVAILABLE UPON REQUEST:

Breathe Free™ Micro-vented wallcovering from Colour & Design can be used to help control un-wanted moisture inside a building envelope. Please request a sample before ordering.

LIMITED WARRANTY:

5 year warranty against manufacturing defects.

STOP... Please read installation instructions on our website for this Radiance Wall™ wallcovering prior to installation.

INSTALLATION NOTE

Random match / Reversible pattern

Repeat: Horizontal: 18" • Vertical: 18"

For specifications and hanging instructions go to: www.colouranddesign.com