

SKUS: CD-CRW-313, CD-CRW-314, CD-CRW-315, CD-CRW-316, CD-CRW-317, CD-CRW-318, CD-CRW-319

PHYSICAL PROPERTIES:

52"/54" (132/137 CM) Vinyl Wallcovering, Type II

Total Weight: 20 oz./lin. yard (620 G/PLM)

13.3 oz./sq. yard (451 G/PSM)

Backing: Osnaburg

Repeat: Horizontal 27" x Vertical 24"

All patterns are stocked in 30 lineal yard bolts and must be ordered in 15 yard increments.

FIRE HAZARD CLASSIFICATION RESULTS:

Tested in accordance with ASTM E-84 Tunnel Test

Class "A" Fire Rated

Flame Spread 15

Smoke Developed 10

In addition, this product meets Type II CCC-W-408A through D & W-101 requirements for Washability, Scrubbability, Abrasion Resistance and Stain Resistance.

PERFORMANCE FEATURES:

- Phthalate-free
- No heavy metals or formaldehyde
- Printed with low VOC inks
- Microventing for permeability is available on a custom order basis

ENVIRONMENTAL ATTRIBUTES:

- Ultra-low emitting - Pass rating under CA 01350
- NSF/ANSI 342 certified for sustainability
- CA Prop 65 compliant

PERMEABILITY, MOISTURE AND MOLD: Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

LIMITED WARRANTY:

5 year warranty against manufacturing defects.

Additional information is available at www.colouranddesign.com

*Inherent with this sophisticated horizontal design
is a refined panel effect.*

INSTALLATION NOTE

random match / reversible pattern

For specifications and hanging instructions go to: www.colouranddesign.com