

**SKUS: CD-CRW-351, CD-CRW-352, CD-CRW-353, CD-CRW-354, CD-CRW-355, CD-CRW-356**

**PHYSICAL PROPERTIES:**

52"/54" (132/137 CM) Vinyl Wallcovering, Type II

Total Weight: 20 oz./lin. yard (620 G/PLM)

13.3 oz./sq. yard (451 G/PSM)

Backing: Non-Woven

Repeat: Horizontal 27" x Vertical 18"

All patterns are stocked in 30 lineal yard bolts and must be ordered in 15 yard increments.

**FIRE HAZARD CLASSIFICATION RESULTS:**

Tested in accordance with ASTM E-84 Tunnel Test

Class "A" Fire Rated

Flame Spread 25

Smoke Developed 30

In addition, this product meets Type II CCC-W-408A through D & W-101 requirements for Washability, Scrubbability, Abrasion Resistance and Stain Resistance.

**PERFORMANCE FEATURES:**

- Phthalate-free
- No heavy metals or formaldehyde
- Printed with low VOC inks
- Microventing for permeability is available on a custom order basis

**ENVIRONMENTAL ATTRIBUTES:**

- Ultra-low emitting - Pass rating under CA 01350
- NSF/ANSI 342 certified for sustainability
- CA Prop 65 compliant

**PERMEABILITY, MOISTURE AND MOLD:** Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

**LIMITED WARRANTY:**

5 year warranty against manufacturing defects.

Additional information is available at [www.colouranddesign.com](http://www.colouranddesign.com)

**INSTALLATION NOTE**

random match / reversible pattern

For specifications and hanging instructions go to: [www.colouranddesign.com](http://www.colouranddesign.com)