

| | | | |
|-----------------------------|---------------------|-------------------------------|---------------------|
| Physical Properties: | Total Weight | U.S. Units | Metric Units |
| | | 20.0 oz./LY | 619 G/PLM |
| | | 13.3 oz./SQ | 451 G/PSM |
| | Fabric Type | Non-Woven | |
| | Material Width | 52/54" | 132/137 cm |
| | Repeat | Horizontal 54" x Vertical 36" | |

Federal Specifications: Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

Fire Hazard Classification Results: **ASTM E-84** Tunnel Test: Class A, Flame Spread: 10; Smoke Developed: 10
Passes NFPA 286 Corner Burn Test

- Performance Features:**
- Phthalate-free
 - No heavy metals or formaldehyde
 - Printed with low VOC inks
 - Microventing for permeability is available on a custom order basis
 - Five year warranty against materials defects

- Environmental Attributes:**
- Ultra-low emitting – Pass rating under CA 01350
 - NSF/ANSI 342 certified for sustainability
 - CA Prop 65 compliant

Permeability, Moisture and Mold: Contains anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration. Breathe Free™ Micro-vented wallcovering from Colour&Design Wall can be used to help control un-wanted moisture inside a building envelope.

INSTALLATION NOTE
FARRAH CHEVRON™ is a reverse match pattern
 For specifications and hanging instructions go to: www.colouranddesign.com