

| Physical Properties: | Total Weight | U.S. Units | Metric Units |
|----------------------|----------------|-------------------------------|--------------|
| | | 20 oz./LY | 619 G/PLM |
| | | 13.3 oz./SQ | 451 G/PSM |
| | Fabric Type | Osnaburg | |
| | Material Width | 52/54" | 132/137 cm |
| | Repeat | Horizontal 54" x Vertical 24" | |

Federal Specifications: Colour&Design Vinyl Wallcovering meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

Fire Hazard Classification

Results: **ASTM E-84** Tunnel Test: Class A, Flame Spread: 20; Smoke Developed: 40
Passes NFPA 286 Corner Burn Test

Performance Features:

- Phthalate-free
- No heavy metals or formaldehyde
- Printed with low VOC inks
- Five year warranty against materials defects

Environmental Attributes:

- Ultra-low emitting – Pass rating under CA 01350
- NSF/ANSI 342 certified for sustainability

Permeability, Moisture and Mold:

Contains anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

INSTALLATION NOTE

Lario™ is a random match / reversible pattern
For specifications and hanging instructions go to: www.colouranddesign.com