

PHYSICAL PROPERTIES:

52"/54" (132/137 CM) Vinyl Wallcovering, Type II

Total Weight: 32 oz./lin. yard (990.4 G/PLM)

21.3 oz./sq. yard (722.1 G/PSM)

Backing: Poly Cotton Osnaburg

Repeat: Horizontal 27" x Vertical 14"

All patterns are stocked in 30 linear yard bolts and must be ordered in 15 yard increments.

FIRE HAZARD CLASSIFICATION RESULTS:

Tested in accordance with ASTM E-84 Tunnel Test

Class "A" Fire Rated

Flame Spread 20

Smoke Development 65

In addition, this product meets Type II CCC-W-408D requirements for Washability, Scrubbability, Abrasion Resistance and Stain Resistance

SUSTAINABILITY, ENVIRONMENT AND HEALTH:

- Meets California 01350 IAQ test requirements for wallcovering
- USGBC LEED
 - Can contribute to CI/NC LEED® EQ 4.1 Low Emitting Materials: Adhesives and Sealants.
 - Can contribute to CI/NC LEED® EQ 4.2 Low Emitting Materials: Paints and Coatings.
 - Can contribute to CI/NC LEED® MR 5.1 Regional Material: If 20% manufactured regionally within 500 miles of jobsite.

All installations must conform to Colour & Design's current Hanging Instructions and Product Technical information.

ANTI-MICROBIAL FEATURES:

This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

LIMITED WARRANTY:

5 year warranty against manufacturing defects.

INSTALLATION NOTE

Pedra™ is a random match / Non-reversible pattern

For specifications and hanging instructions go to: www.colouranddesign.com