

Physical Properties:	Total Weight	U.S. Units	Metric Units
		20 oz./LY	619 G/PLM
		13.3 oz./SQ	451 G/PSM
	Fabric Type	Osnaburg	
	Material Width	52/54"	132/137 cm
	Repeat	Horizontal 54" x Vertical 24"	

Federal Specifications: Colour&Design Vinyl Wallcovering meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

Fire Hazard Classification

Results: **ASTM E-84** Tunnel Test: Class A, Flame Spread: 15; Smoke Developed: 25
Passes NFPA 286 Corner Burn Test

Performance Features:

- Phthalate-free
- No heavy metals or formaldehyde
- Printed with low VOC inks
- Five year warranty against materials defects

Environmental Attributes:

- Ultra-low emitting – Pass rating under CA 01350

Permeability, Moisture and Mold:

Contains anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.
Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

INSTALLATION NOTE
Snowdrift Texture™ is a random match/reversible pattern
 For specifications and hanging instructions go to: www.colouranddesign.com